NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON (Please type or print)

State	Well	No. 265/30E-51	5
~	_		

(Do not write above this line)

State	Well N	<u>, (X</u>	62/20E-206
State	Permit	No.	Anne 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

(1) OWNER:	(10) LOCATION OF WELL:
Name H. P. Reid	County Harney Driller's well number
Address 5605 Thex N.E.	SW 14 NW 14 Section 5 T. 265 R. 306 W.M.
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well K Deepening Reconditioning Abandon I If abandonment, describe material and procedure in Item 12.	
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 80 ft.
Jetted Domestic Industrial Municipal	Static level 98 ft. below land surface. Date
□ Bored □ Irrigation Test Well □ Other □	Artesian pressure lbs. per square inch. Date
(5) CASING INSTALLED: Threaded Welded Welded To the Diam. from the to the Gage 250 ft. Gage To Diam. from ft. to ft. Gage ft. Gag	(12) WELL LOG: Diameter of well below casing
(6) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in,	Soil; sandy - brown 0 1
perforations fromft. toft.	tyse, comented 1 98 98
perforations from ft. to ft	clay stone black 98 101
(E) COPPER	baselt, black 101 185 185 187
(7) SCREENS: Well screen installed? ☐ Yes No	basalt, black 187 357
Manufacturer's Name	
Type Model No Diam Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED
a pump test made? Yes No If yes, by whom?	AFRICA 1000 - 110 TO 2000
Yield: gal./min. with ft. drawdown after hrs.	W. RESOURCE AUG 191980
n n n	WATER RESOURCES DEP
n n n	SALEM, OREGON
er test D gal./min. with O ft. drawdown after hrs.	
Artesian flow g.p.m.	
Temperature of water 54 Depth artesian flow encountered	Work started 2-15 1980 Completed 2-22 1980
(9) CONSTRUCTION:	Date well drilling machine moved off of well 2-22 1980
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface to .20 ft.	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore below seal	[Signed] Daniel P. Merry Date 3-7, 1980
Number of sacks of cement used in well seal \$\frac{1}{2} \text{Sacks}\$ How was cement grout placed? \$\frac{1}{2} \text{OUT} \text{DUMP} \text{E}\$	(Drilling Machine Operator) Drilling Machine Operator's License No. 1285
How was cement grout placed? grout pump &	Figure 170.
	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name Daniel P. Merrill
Old any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)
Cype of water? depth of strata	Address 150x 250, Dams, Ore,
Method of sealing strata off	[Signed] Daniel P. Merry
Was well gravel packed? ☐ Yes 🔀 No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 728 Date 3-7- 1980
/IICT AND VINCE	