

- Legend**
- UTILITY MARK (PI SET WITH PLASTIC CAP STRAPPED STATION FOR P.L.S. & REBAR) NO ID CAP
 - ◆ HEAVY DUTY POINT
 - ▲ STONE (PI)
 - ▲ P.K. NAIL SET
 - TREE MARKED IN 3 WAYS IN SQUARE CONDITION MARKED ON UTILITY MARK
 - PINE (PI)
 - ✕ POLE
 - ✕ POINT OF BEGINNING

NOTES:

All, and all, were called for as corners of a minimum 2' in diameter in sound condition and have 3 inch marks about their top.


THE SURVEY BEING SUBJECT TO ANY EMBLEMEN, RIGHTS, OR CLAIMS AND ANY OTHER CONVEYANCES WHICH MAY BE OF RECORD OR NOT AND HAVE APPLICABLE THE SAME HEREIN.

All Right-of-Way shown and described are located on the referenced road these Owners Hold.

Certification:

I do hereby certify that the foregoing was by me personally performed or supervised by me, and that the same is a true and correct copy of the original as shown to me by the owner and that the same is a true and correct copy of the original as shown to me by the owner and that the same is a true and correct copy of the original as shown to me by the owner.

[Signature]
 J.A. STATION, R.P. 2000, Dade



Source of Title

Being a part of the same books as described in deed book 65 page 464 of the Clinton County Clerk's Office.

Call's Down Corner of Bound

LINE	BEARING	DISTANCE
L1	S69°28'01"W	22.96'
L2	S81°10'14"W	28.62'
L3	S61°10'30"W	24.69'
L4	S44°01'44"W	36.02'
L5	S43°38'47"W	60.18'
L6	S03°19'24"W	61.64'
L7	S91°24'44"W	43.44'
L8	S66°30'59"W	63.42'
L9	N66°58'32"W	66.56'
L10	N78°41'51"W	52.17'
L11	N60°00'18"W	37.52'
L12	S64°54'44"W	64.78'
L13	S78°28'54"W	36.54'
L14	S44°21'22"W	26.54'
L15	S78°27'41"W	27.62'
L16	S66°28'12"W	37.94'
L17	S61°02'41"W	63.40'
L18	S94°42'18"W	56.42'
L19	S71°12'26"W	59.02'
L20	S64°23'50"W	108.20'
L21	N60°18'02"W	24.30'
L22	N64°44'28"W	77.71'
L23	S73°56'24"W	128.71'
L24	S30°18'24"W	50.85'
L25	S71°05'22"W	11.22'
L26	S44°26'54"W	17.11'
L27	S61°34'50"W	42.28'
L28	S19°12'50"W	46.73'
L29	S64°41'47"W	37.63'
L30	S81°21'16"W	100.01'
L31	S90°48'09"W	136.45'
L32	S73°28'28"W	111.14'
L33	N61°46'07"W	228.45'
L34	N72°16'28"W	68.73'
L35	N11°59'24"W	75.40'
L36	N64°12'51"W	47.86'
L37	S64°08'14"W	62.66'
L38	N64°27'45"W	50.25'
L39	N00°01'04"W	144.63'
L40	N00°24'45"W	41.67'
L41	N00°21'51"W	159.14'

Top Table Data

LINE	BEARING	DISTANCE
L1	N61°28'16"W	49.26'
L2	N46°07'32"E	77.05'
L3	N64°20'51"E	42.61'
L4	N62°58'16"E	46.51'
L5	N64°58'59"E	27.79'
L6	N71°43'20"E	24.53'
L7	N61°02'18"E	62.57'
L8	N70°40'54"E	24.49'
L9	N62°05'59"E	42.62'
L10	N62°45'59"E	76.59'
L11	N64°12'26"E	106.14'
L12	S64°54'44"W	74.64'
L13	S64°54'44"W	58.72'
L14	S62°46'01"E	34.00'
L15	S00°26'14"E	49.55'
L16	S41°20'12"E	10.11'
L17	S41°20'12"E	10.11'
L18	S40°01'15"E	131.65'
L19	S40°01'15"E	45.59'
L20	S40°01'15"E	28.11'
L21	S44°11'59"E	21.49'
L22	S60°29'03"W	181.4'

Clinton Surveying
 286 Hughes Road
 Albany, Kentucky 42602

Tan Hunt
 Survey Plot No.

JASON R. P. L.S. 2000
 448 E. Main St.
 Albany, KY 42602

START OF FIELD SURVEY: 08-30-21
 FINAL OF FIELD SURVEY: 12-01-21

SCALE: 1"=300'
 DATE: 12/14/21
 DRAWN BY: S.B./J.S.
 CHECKED BY: J.A.S.